

BRINGING MODERN COMFORT TO YOUR HOME



Applications



Pressure Boosting

Energy savings, unforgettable shower experiences and strong, constant water pressure for your daily needs around the home. The CM-PT series pressure booster system with pneumatic tank gives you a host of extraordinary benefits.

The pneumatic tank smoothes flow from faucets, reduces the number of start/stops, eliminates pulsations and water hammer. One of the advantages of a pneumatic tank is that they can dispense up to half of their capacity of water without the pump switching on, resulting in less wear and tear and greater energy savings.



Water Supply

With superior Danish technology, sterling quality and the fact that only Grundfos pumps are SIRIM certified, you are assured total peace of mind and satisfaction when you choose Grundfos.

Grundfos, bringing modern comfort to your home.



Residential

Model	Discharge Pressure : PSI						Tank Size	Pre-set Operating Pressure (PSI)	Port Size (BSP)	Length x Height x width (mm)
	18	20	29	36	51	55				
	Output : Litre / minute									
CM3-3 PT 0.50kw	72	70	50	27	-	-	8 Litre	18 - 38	1" inlet 1" outlet	310 x 600 x 270
CM3-5 PT 0.50kw	-	-	70	62	41	33	18 Litre	29 - 58	1" inlet 1" outlet	350 x 650 x 290
CM5-4 PT 0.67kw	-	-	100	87	26	-	18 Litre	29 - 50	1¼" inlet 1" outlet	370 x 650 x 290

Features & Benefits



Product certified by SIRIM



Quiet operation



2 years warranty



Energy saving



Quality assurance



Longer life span



Easy installation

将时尚舒适 融入家居生活



用途



增强水压

节省能源、令人回味无穷的淋浴体验，以及强劲稳定的水压供家居日常用途，让具备气压缸的CM-PT增压器系统系列为您带来种种出色的优点。

气压缸使水龙头水流顺畅，减少开停次数，同时也消除水压脉动和水击作用。此特色的优点之一是气压缸可以排出多达一半水量，而无需启动水泵，因此减少磨损，而且更节省能源。

Grundfos采用优越丹麦科技和高质量的住家式压水泵，获得SIRIM认证，因此选择Grundfos绝对令您安心满意。

让Grundfos为您的住家增添现代安逸享受。



水供



住宅

型号	排放压力:PSI						缸容量	预设操作水压 (PSI)	端口尺寸 (BSP)	长度x高度x宽度 (毫米)
	18	20	29	36	51	55				
出水率: 每分钟公升										
CM3-3 PT 0.50kw	72	70	50	27	-	-	8公升	18-38	1寸入口 1寸出口	310 x 600 x 270
CM3-5 PT 0.50kw	-	-	70	62	41	33	18公升	29-58	1寸入口 1寸出口	350 x 650 x 290
CM5-4 PT 0.67kw	-	-	100	87	26	-	18公升	29-50	1 1/4寸BSP入口 1寸出口	370 x 650 x 290

特色和好处



SIRIM认证产品



安静操作



2年保修期



节省能源



品质保证



耐久可靠



安装简易

GRUNDFOS PUMPS SDN BHD (202527-A)

7, Jalan Peguam U1/25
Glenmarie Industrial Park
40150 Shah Alam, Selangor,
Malaysia
Tel : +603-5569 2922
Fax : +603-5569 2866
Email: gfosmy1@grundfos.com
www.grundfos.com.my



Cert No. KLR0402930

Branch Offices

Northern & East Coast
10, Ground Floor,
Jalan Todak 4, Bandar Sunway,
13700 Seberang Jaya,
Penang
Tel : +604-818 3779
Fax : +604-818 3848

East Malaysia

Lot 8, Lorong Industri Warisan 1,
Taman Industri Warisan Indah,
Mile 7, Old Tuaran Road
88450 Inanam, Kota Kinabalu,
Sabah
Tel : +6088-380 663/-383 663
Fax : +6088-383 621

GRUNDFOS